



TRITIUM COLLECTION SYSTEM F&J MODEL TCS-3000E

NOTABLE FEATURES:

- Microprocessor controlled electronics
- Flow rate measurements and volume totalizations are corrected to a factory settable reference Temperature and Pressure
 - Classical STP 0°C, 1 Atm
 - Normal T and P 20°C, 1 Atm
 - Modified Normal T and P 70°F, 1 Atm
 - Standard Ambient T and P 25°C, 1 Atm
- RS-232 Port
- LED Display
- Precision machined orifice
- Flow rate accuracy within $\pm 4\%$ F.S.
- Flow rate / volume options:
 - sccm / scc
 - SLPM / SL
- 220-240VAC; 50/60Hz, single phase



GENERAL DESCRIPTION:

The Model TCS-3000E Tritium Collection System is a tritium collection system consisting of a diaphragm pump, electronic airflow regulator and 2 removable polycarbonate Indicating Silica Gel columns. The flow and volume of air passing through the system is adjusted and measured by a microprocessor controlled Digital Flow Meter (DFM). The DFM utilizes a precision-machined orifice to measure flowrate. The DFM displays on-board calculations on a bright large character LED display. Flowrate and totalized volume corrected to a reference T and P and elapsed time are displayed.

Multiple operator selectable data download frequencies are available through the RS232 port for collection and/or storage of real-time data.

The unit is designed for continuous indoor use. Please consult the product specifications for the design temperature range and the installation category.

The typical operating flow range is 100 - 400 sccm (0,10 – 0,4 LPM).

Rev.: 30 April 2008

TCS-3000E Tritium Collection System (220 – 240VAC)

SPECIFICATIONS:

PUMP TYPE:	Diaphragm
CAPACITY:	Maximum capacity dependent upon pump size and flow sensor design.
POWER REQUIREMENTS:	220 – 240VAC; 50/60 Hz; 1 ampere; single phase
CIRCUIT BREAKER PROTECTION:	5 amperes
ELECTRICAL CORD:	All temperature, 3-wire, 16 gauge
DIMENSIONS:	9”D × 24”W × 20”H
WEIGHT:	67 lbs. (30,3 kg)
INSTALLATION CATEGORY:	Pollution Degree 2

ELECTRONIC SPECIFICATIONS

MEASUREMENT ACCURACY

Air flow:	± 4% of full scale
Temperature:	± 0.9°F (0.5°C) (Not displayed)
Barometric Pressure:	± 0.6 inches Hg (Not displayed)

OPERATING TEMPERATURES: 0° - 104°F (-17° - 40°C)*

STORAGE TEMPERATURE: -20° - 122°F (-28° - 50°C)

* With optional heating system

CALIBRATION: Calibration-verification once per year; Factory calibration as needed.

COMMUNICATIONS INTERFACES: RS-232

ON-BOARD CALCULATIONS

- Flow calculation from differential pressure value corrected to a reference T and P
- Elapsed Time
- Cumulative Volume corrected to a reference T and P

OPTIONS:

- FlashCard Datalogger system for collection and storage of real-time data exiting the RS232 port.
- FlashCard data storage device: P/N: 232FCDS
- FlashCard 128 MB; P/N: 372239
- FlashCard Reader; P/N: 515177

NOTE:

Other tritium absorbing media may be utilized, such as molecular sieve, water or ethylene glycol.